

Machine receivers are placed on a earthmoving machine such as backhoe or grader and indicate the height of the bucket or blade in relation to a red rotating laser beam.

EARTHMOVERS

CIVIL CONTRACTORS

MODEL OPTIONS

MR706 Magnetic Mount

MR706D Magnetic with in cab

MR708 Clamp Mount

MR706D Clamp with in cab

FEATURES

360° Sensors

250mm Reception

Last Received Height Flash

Fine/Coarse Accuracy

Water and Dust Tight

Ni-mh Battery and Charger

12/24V Machine Operation

2 Year Warranty



MR706 OR MR708, Charger, 12/24V Power Cable and Hard Case.

MR706/MR706D

MR708/MR708D

Machine Receiver with or without in cab repeater unit

Suitable For Red Beam class 2/3/3r rotating lasers



VIDEO LINK



BROCHURE LINK



MR706D OR MR708D, In Cab Repeater Unit, Charger, 12/24V Power Cable, In Cab Cable and Hard Case.

EARTHMOVERS

CIVIL CONTRACTORS

MR825WD

Machine Receiver with wireless in cab repeater unit

Suitable For Red Beam class 3/3r rotating lasers
(can be used with green beam and red class 2 rotating lasers with reduced range)

FEATURES

360° Sensors

260mm Reception

Two Way RF Transmission

Wireless In-Cab Repeater

Blade Tilt/Level Indication

Plumb Swing Indication

Last Received Height Flash

Magnetic and Clamp Mounts

±5mm/±10mm/±20mm Accuracy

Laser Range up to 200m

Water and Dust Tight

Ni-mh Battery and Charger (receiver)

2 Year Warranty



VIDEO LINK



BROCHURE LINK



MR825, WRD10 RF In Cab Repeater Unit, Charger, Magnetic & Clamp Receiver Mounts, Windscreen Suction, Magnetic & Clamp Repeater Mounts and Hard Case.

Model Number

Web Site

Laser Level Compatibility

Laser Type

Reception Range

Accuracy Settings

Machine Power Operation

Rechargeable internal Battery

Two Way RF Range

Reception Angle

Reception Height

Blade Tilt Accuracy

Plumb Swing Accuracy

Last Received Height Indication

Mounting

IP Dust/Water Resistance Rating

Warranty (automatic)

MR706, MR706D, MR708, MR708D

<http://www.redbacklasers.com.au/mr706.html>

Rotating Red Visible Beam

Pipe Laser

300m

± 3mm-12mm, ± 5mm-25mm (depends on beam diameter)

12/24V

Ni-mh Battery and Charger

NO

360°

250mm

NO

NO

Flash (high or Low)

MR706/D Magnetic, MR708/D Clamp

IP66

2 Years

MR825

<http://www.redbacklasers.com.au/mr825.html>

Rotating Red Visible Beam

Pipe Laser

300m

±5mm, ±10mm, ±20mm

12V

Ni-mh Battery Pack and Charger

10m

360°

250mm

±0.5°, ±1.5°, ±2.5°

±0.5°, ±1.5°, ±2.5°

Flash (high or Low)

Magnetic and Clamp

IP66

2 Years